

TRINCA®

意大利 特意佳

T.N.6E-PS4200

型號
mod.



Regional Agent 大中華區域代理:

A&A Consultant 香港 A&A 諮詢

☎ : www.hkaac.net

@: info@hkaac.net

☎: +852-9023 4800

☐: PO Box 143, Tung Chung, HONG KONG (香港)

型號. T.N.6E-PS 4200 mod.

超重負載型金屬絲網織機

Weaving machine Appropriate to weave heavy fabrics PZ from steel

T = 技術織物織機
N = 1 劍桿引緯
6 = 凸輪組數
E = 油浴槽內共軛凸輪
PS = 超重負荷型結構
4200 = 織造幅寬

技術參數:

- 織造幅寬:1500 - 4200 毫米;
- 織造速度可調: 0 - 60 轉/分鐘;
- 模組式鋼機構;
- 電子調節偏轉羅拉,並可根據織物數據記憶軸位置.
- 直接捲取;
- 經紗裝置帶 2組後端可調離式經軸.
- 經紗總張力 10,000 +(10)牛頓米;
- 總打(卡)緯力 12,000十牛頓米.

電子旋轉式多臂機 特意佳型號 R.E.R 2-8

R = 多臂機
E = 電子式
R = 旋轉式
2 = 雙吊綜座 (連桿由上端及下端作連結)
8 = 頁綜框驅動

- 4 組吊綜座於綜框上端
- 4 組吊綜座於綜框下端
- 電腦驅動及管控;
- 開口方式: 開式開口和閉式開口經由個人電腦編程;
- 極簡易的綜框“0”位設定;
- 每頁綜框的各項參數均可單獨設置;
- 綜框的開口時間曲線和停頓均可調整;
- 綜框的開口時間曲線相位均可調移;

織機控制裝置:

全方位的機器控制,包括所有的參數設定和操作功調節均由特意佳 TRINCA織機管理系統專項研發的電器控制系統處理.特意佳管理系統建基於載有視窗(Windows)CE作業系統的工業級個人電腦,管控全部參數以及所有的控制功能.全體電子和電器控制裝置均安裝在主電器櫃內.

T = loom
N = weft insertion with 1 rapier tape
6 = no. of slay driving cam groups
E = driven by eccentric curves running in oil bath
PS = extra strong
4200 = weaving width

TECHNICAL SPECIFICATIONS:

- weaving width: max. 4200 mm – min. 1500 mm;
- adjustable speed from 0 up to max. 60 rpm
- maximum warp tension 10.000 daNm
- maximum beat-up tension 12.000 daNm
- modular steel structure;
- direct take-up;
- warping device including 2 posterior removable warp beams;
- electronically adjustable deflection rollers with possibility to save the position of the beams in the article data.

ELECTRONIC ROTATING DOBBY MACHINE TRINCA TYPE R.E.R 2-8

R = dobby
E = electronically controlled
R = rotating
2 = duplex connecting rods (shafts are connected from top and bottom)
8 = no. of heddle frames

- 4 connections for each of the top frames
- 4 connections for each of the bottom frames
- PC driven and controlled;
- possibility to weave with opened or closed shed;
- possibility to align the frames onto point “0”;
- possibility to control and adjust each single frame in manual mode;
- possibility to adjust the frames standstills;
- possibility to adjust the frame change phase.

LOOM CONTROL DEVICE:

The complete loom control, all data settings and operating function adjustments are carried out by the TRINCA electronic control device and the especially by TRINCA developed loom managing. All electronic and electric control devices are installed inside the main switchboard and all data, as well as loom driving and control functions are developed by an industrial PC with software windows CE.