

T.N.E.
mod.
型號

TRINCA®

意大利 特意佳



Regional Agent 大中華區域代理:



A&A Consultant 香港 A&A 諮詢



: www.hkaac.net

@: info@hkaac.net

☎: +852-9023 4800

☐: PO Box 143, Tung Chung, HONG KONG (香港)

國際市場上對高品質產品需求日趨增加,小批量多品種乃大勢所趨,因此織機生產廠需向業界提供極靈活而又可靠的系統。

憑藉數十年的經驗,我們研發出嶄新的**T.N.E.**系列織機,重大的技術改進,完全滿足業界全方位的訴求:極具靈活性,產出高品質,提高生產力。

新穎的**T.N.E.** 系列織機具有下列技術特徵:

1. 以運動基理已註冊專利的寬劍桿夾持紗線,能極有效維持引緯全過程保持最佳張力
2. 筘座運動裝置由油浴共軛凸輪驅動,並於打緯時予以充分開口停頓時間
3. 布捲及張力由3羅拉壓棍夾持裝置執行
4. 電子控制送經和捲取,可數字化直觀輸入需要的絲網織造目數
5. 綜框運動由凸輪或多臂機擔當
6. 可根據客戶要求提供機外分離式捲布系統,以達到快速了機更換品種的應效
7. 織機採用模組方式構建,同一機型可據客戶不同要求設置各異共軛凸輪組合

織機根據不同的共軛凸輪組數配置,例如配: 2,3,4,5,6組, 織機型號分別命名為: **T.N.2E - T.N.3E - T.N.4E**以此類推...

The international market has an ever increasing demand for products of high quality yet frequently, in small quantities.

The manufactures try to meet this new requirement by using machinery that offers higher flexibility and reliability.

Backed by many years of experience we have developed a new **"T.N.E." range** of weaving machines incorporate substantial technological improvements that make them more flexible while ensuring a high quality fabric with, at the same time, an important increase in productivity.

The new **T.N.E.** range incorporates the following technical features:

1. weft wire insertion by only band rapier with a patented kinematic mechanism that keeps the weft wire under tension
2. slay movement driven by complementary cams in oil bath with a slay dwell during beat up
3. fabric wind-up and tensioning by 3 roller nipping unit
4. electronically controlled let-off and take-up units with digital mesh number input
5. heald frame control by a cam motion unit or a dobby
6. fabric wind-up on separate cloth beam that can easily be removed or, upon request, outside the weaving machine on a separate wind-up
7. modular steel frame construction which allows setting up the same machine type with a different number of complementary cam groups.

The weaving machines are differentiated by the complementary cam groups to be mounted 2,3,4,5,6 and are designated **T.N.2E - T.N.3E - T.N.4E.....**

方型絲網織物規格表 - Square mesh fabric schedule

目 Mesh/25,4 mm	10	20	30	40	50	60	80	100	200
緯 Pitch / mm.	2,54	1,27	0,85	0,635	0,508	0,423	0,317	0,254	0,127
織造幅寬所對應的最大線徑 Max wire diameter for weaving width	1300 mm	0,70	0,50	0,35	0,28	0,21	0,17	0,13	0,05
	1600 mm	0,65	0,48	0,32	0,25	0,20	0,16	0,12	0,05
	2100 mm	0,60	0,45	0,30	0,24	0,18	0,15	0,11	0,05

技術參數:

電子控制前後調節器: 8.5 - 3000 目/25.4 毫米

紗線原料: 鐵,銅,青銅,不鏽鋼,高強鋼,鋁,合成材料.

線徑: 0.05 - 0.50 毫米 最大打緯張力 3000 公斤 / 米

織造組織: 可織2,3,4,5,6頁綜框

Technical features:

Electronic controlled rear and front regulator: from 8,5 to 3000 mesh/25,4 mm

Wire material: iron, copper, brass, stainless steel, high tensile steel, aluminium, synthetic materials.

Wire diameter: 0,05 up to 0,50 mm. Max beat-up tension: 3000 kg

Weaving possibilities: with 2 or 3 or 4 or 5 or 6 healdframes

織造幅寬 毫米. Weaving width in mm.	1300	1600	2100
織造速度達可: 緯/分鐘 Max speed / rpm	220	200	160